



CE70H160DNGI

CoreGaN 700V GaN HEMT

Description

The CE70H160DNGI Series 700V, 160mΩ gallium nitride (GaN) FETs are normally-off devices.

Coreenergy GaN FETs offer better efficiency through lower gate charge, faster switching speeds, and lower dynamic on-resistance, delivering significant advantages over traditional silicon (Si) devices.

Coreenergy is a leading-edge wide band gap supplier with world-class innovation .

Application

- Adapter
- Renewable energy
- Telecom and data-com
- Servo motors
- Industrial
- Automotive

General Features


Easy to drive—compatible with standard gate drivers
Low conduction and switching losses
RoHS compliant and Halogen-free

Benefits


Increased efficiency through fast switching
Increased power density
Reduced system size and weight

Ordering Information


Part Number	Package	Package Configuration
CE70H160DNGI	DFN 8*8	Source



Top



Bottom



Circuit Symbol

Features

BV_{DSS}	$R_{DS(ON)}$	I_{DS}	Q_G
700V	160mΩ	14A	8.7nC



Absolute Maximum Ratings

$T_c = 25^\circ\text{C}$ unless otherwise stated

Symbol	Parameter		Limit value	Unit
V_{DSS}	Drain to source voltage ($T_J = -55^\circ\text{C}$ to 150°C)		700	V
$V_{(TR)DSS}$	Drain to source voltage-transient ^a		850	
V_{GSS}	Gate to source voltage		-20~+20	
I_D	Continuous drain current @ $T_c = 25^\circ\text{C}$ ^b		14	A
	Continuous drain current @ $T_c = 125^\circ\text{C}$ ^b		6	
I_{DM}	Pulse drain current (pulse width: 10 μs)		26	A
P_D	Maximum power dissipation @ $T_c = 25^\circ\text{C}$		83	W
T_c	Operating temperature	Case	-55~150	$^\circ\text{C}$
T_J		Junction	-55~150	$^\circ\text{C}$
T_s	Storage temperature		-55~150	$^\circ\text{C}$

a. In off-state, spike duty cycle $D < 0.01$, spike duration $< 1\mu\text{s}$

b. For increased stability at high current operation



CE70H160DNGI

Thermal Resistance

Symbol	Parameter	Limit value	Unit
$R_{\theta JC}$	Junction-to-case	1.5	°C /W



Electrical Parameters

$T_J = 25^\circ\text{C}$ unless otherwise stated

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
Forward Device Characteristics						
$V_{(BL)DSS}$	Drain-source voltage	700	-	-	V	$V_{GS} = 0V$
$V_{GS(th)}$	Gate threshold voltage	1.8	2.3	2.8	V	$V_{DS} = 1V, I_{DS} = 1mA$
$\Delta V_{GS(th)}/T_J$	Gate threshold voltage temperature coefficient	-	-7	-	mV/ $^\circ\text{C}$	
$R_{DS(on)}$	Drain-source on-Resistance	-	160	210	m Ω	$V_{GS} = 10V, I_D = 4A, T_J = 25^\circ\text{C}$
		-	340	-		$V_{GS} = 10V, I_D = 4A, T_J = 150^\circ\text{C}$
I_{DSS}	Drain-to-source leakage current	-	2	10	μA	$V_{DS} = 700V, V_{GS} = 0V, T_J = 25^\circ\text{C}$
		-	5	100		$V_{DS} = 700V, V_{GS} = 0V, T_J = 150^\circ\text{C}$
I_{GSS}	Gate-to-source forward leakage current	-	-	± 100	nA	$V_{GS} = \pm 20V$
C_{ISS}	Input capacitance	-	410	-	pF	$V_{GS} = 0V, V_{DS} = 400V, f = 1MHz$
C_{OSS}	Output capacitance	-	24	-		
C_{RSS}	Reverse capacitance	-	0.97	-		
Q_G	Total gate charge	-	8.7	-	nC	$V_{DS} = 400V, V_{GS} = 0V \text{ to } 10V, I_D = 1A$
Q_{GS}	Gate-source charge	-	2.3	-		
Q_{GD}	Gate-drain charge	-	2.7	-		
Q_{OSS}	Output charge	-	36	-	nC	$V_{GS} = 0V, V_{DS} = 0V \text{ to } 400V, f = 1MHz$
$t_{D(on)}$	Turn-on delay	-	6	-	ns	$V_{DS} = 400V, V_{GS} = 0V \text{ to } 10V, I_D = 2.1A, R_{G-on(ext)} = 6.8\Omega, R_{G-off(ext)} = 2.2\Omega, L = 250\mu H$
t_R	Rise time	-	5.9	-		
$t_{D(off)}$	Turn-off delay	-	13.1	-		
t_F	Fall time	-	19.6	-		



Electrical Parameters

T_j=25°C unless otherwise stated

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
Reverse Device Characteristics						
V _{SD}	Source-Drain reverse voltage	-	2.5	-	V	V _{GS} =0V, I _S =10A
t _{RR}	Reverse recovery time	-	14	-	ns	I _S =10A, V _{DD} =400V, di/dt=165A/μs
Q _{RR}	Reverse recovery charge	-	6.5	-	nC	



Typical Characteristics

$T_j = 25^\circ\text{C}$ unless otherwise stated




Figure 1. Typical Output Characteristics $T_j = 25^\circ\text{C}$




Figure 2. Typical Output Characteristics $T_j = 125^\circ\text{C}$




Figure 3. Typical Transfer Characteristics ($V_{DS} = 10\text{V}$)




Figure 4. Normalized On-resistance



Typical Characteristics

$T_j = 25^\circ\text{C}$ unless otherwise stated




Figure 5. Typical Capacitance (f=1MHz)




Figure 6. Typical Gate Charge ($V_{DS}=400\text{V}$, $I_D=1\text{A}$)




Figure 7. Typical C_{OSS} Stored Energy




Figure 8. Typical Q_{OSS}



Typical Characteristics

$T_J = 25^\circ\text{C}$ unless otherwise stated




Figure 9. Channel Reverse Characteristics $T_J = 25^\circ\text{C}$




Figure 10 Channel Reverse Characteristics $T_J = 125^\circ\text{C}$




Figure 11. Transient Thermal Resistance




Figure 12. Power Dissipation



Typical Characteristics

$T_j = 25^\circ\text{C}$ unless otherwise stated




Figure 13. Safe Operating Area $T_j = 25^\circ\text{C}$




Figure 14. Switching times with inductive load

$V_{DS} = 400\text{V}$, $V_{GS} = 0\text{V to } 10\text{V}$, $I_D = 2.1\text{A}$,
 $R_{G-on(ext)} = 6.8\Omega$, $R_{G-off(ext)} = 2.2\Omega$, $L = 250\mu\text{H}$




Figure 15. Switching times with waveform




CE70H160DNGI


PACKAGE DIMENSIONS

DFN8x8-8L-1.10-A


Top view



Bottom view



Side view(left/right)



Symbol	Min. (mm)	Mean. (mm)	Max. (mm)
A	1.05	1.10	1.15
A1	0	0.02	0.05
A2	0.203REF		
D	7.9	8	8.1
E	7.9	8	8.1
D1	0.9	1	1.1
D2	3.1	3.2	3.3
D3	2.7	2.8	2.9
E1	6.9	7	7.1
E2	0.4	0.5	0.6
E3	0.4	0.5	0.6
E4	6.9	7	7.1
e	1.9	2	2.1
b	0.9	1	1.1
L	0.4	0.5	0.6



CE70H160DNGI

Revision history

Major changes since the last revision

Revision	Date	Description of changes
1.0	2024-07-10	Initial release
2.0	2025-01-02	Optimize application platform testing